

---

**CONVEX**  
**Internet Services**  
**Master Index**

---



Second Edition  
November 1990

CONVEX Computer Corporation  
Richardson, Texas USA

---

**CONVEX**  
**Internet Services**  
**Master Index**

Copyright 1990 CONVEX Computer Corporation  
All rights reserved.

This document is copyrighted. It may not in whole or part, be copied, duplicated, reproduced, translated, electronically stored, or reduced to machine-readable form without prior written consent from CONVEX Computer Corporation.

Although the material contained herein has been carefully reviewed, CONVEX Computer Corporation (CONVEX) does not warrant it to be free of errors or omissions. CONVEX reserves the right to make corrections, updates, revisions or changes to the information contained herein. CONVEX does not warrant the material described herein to be free of patent infringement.

Unless provided otherwise in writing with CONVEX Computer Corporation (CONVEX), the program described herein is provided as is without warranty of any kind, either expressed or implied, including, but not limited to the implied warranties of merchantability and fitness for a particular purpose. Some states do not allow the exclusion of implied warranties. The above exclusion may not be applicable to all purchasers because warranty rights can vary from state to state. In no event will CONVEX be liable to anyone for special, collateral, incidental, or consequential damages, including any lost profits or lost savings, arising out of the use or inability to use this program. CONVEX will not be liable even if it has been notified of the possibility of such damage by the purchaser or any third party.

CONVEX and the CONVEX logo ("C") are registered trademarks of CONVEX Computer Corporation

ConvexOS is a trademark of CONVEX Computer Corporation.

Ethernet is a trademark of Xerox Corporation.

HYPERchannel is a trademark of Network Systems Corporation.

UltraNet is a trademark of UltraNetwork Technologies, Incorporated.

UNIX is a registered trademark of AT&T Bell Laboratories.

Printed in the United States of America

---

## Revision Information for

### CONVEX Internet Services Master Index

---

Edition	Document No.	Description
Second	710-003030-201	Released with CONVEX Internet Services V9.0, November 1990. This manual was previously entitled <i>CONVEX Networking Utilities Master Index</i> .
First	710-003030-200	Released with CONVEX UltraNet Interface software V1.0 and ConvexOS V8.0, December 1989.



---

# Index

\$INCLUDE files, name server smg-9-5  
.rhosts file user-2-2  
    permissions user-2-3  
/.rhosts file user-2-2, smg-A-10  
/etc/ftpusers file, see *ftpusers file*  
/etc/gateways file, see *gateways file*  
/etc/group file, see *group file*  
/etc/hosts file, see *hosts file, host database*  
/etc/hosts.equiv file, see *hosts.equiv file*  
/etc/ifconfig, see *ifconfig command*  
/etc/inetd.conf file, see *inetd.conf file*  
/etc/named.boot file, see *named.boot file*  
/etc/netgroup file, see *netgroup file*  
/etc/networks file, see *networks file*  
/etc/passwd file, see *passwd file*  
/etc/protocols file, see *protocols file*  
/etc/rc script, see *rc script*  
/etc/rc.local script, see *rc.local script*  
/etc/resolv.conf file, see *resolv.conf file*  
/etc/route, see *route command*  
/etc/rpc file, see *rpc file*  
/etc/services file, see *services file*  
/etc/shells file user-4-6  
/etc/use\_nameserver file, see *use\_nameserver file*  
/ioconfig file smg-2-1 to smg-2-6  
    adding network interfaces smg-2-5  
    displaying smg-2-1  
    Ethernet entries smg-2-5  
    HYPERchannel entries smg-2-6, smg-5-3  
    installing device drivers smg-5-10  
    ordering of interfaces smg-4-1  
    solving configuration problems smg-5-4  
    UltraNet entry smg-2-6  
/usr/etc/unetcf aadd command, see *unetcf aadd*  
/usr/etc/unetcf adel command, see *unetcf adel*  
/usr/etc/unetcf adis command, see *unetcf adis*  
/usr/etc/unetcf madd command, see *unetcf madd*  
/usr/etc/unetcf mdel command, see *unetcf mdel*  
/usr/etc/unetcf radd command, see *unetcf radd*  
/usr/etc/unetcf rdel command, see *unetcf rdel*  
/usr/etc/unetcf rdis command, see *unetcf rdis*  
/usr/etc/unetd.conf file, see *unetd.conf file*  
/usr/lib/conf/bind directory smg-9-1, smg-9-25,  
    smg-9-26  
/usr/lib/conf/bind/setup directory smg-9-19

/usr/lib/firmware/uv directory smg-6-2  
/usr/local/domain directory smg-9-5  
/usr/tmp/named.stats file smg-9-21  
/usr/tmp/named\_dump.db file smg-9-21  
~/rhosts file smg-8-6, smg-A-10  
~/ftp/pub directory smg-8-7

---

## A

A400 HYPERchannel Adapter  
    assigning unit value smg-5-6  
    recommended MTU setting smg-5-9  
    setting timeout value smg-5-1  
    setting unit value smg-5-1  
    solving configuration problems smg-5-7  
    testing hardware configuration smg-5-4  
aborting remote logins user-3-2  
accept  
    blocking ipc-4-8  
    connection request ipc-5-14  
    relevant man pages ipc-4-9  
    use by server process ipc-4-18  
    use with inetd ipc-6-16  
    use with socket connections ipc-4-7  
    uses ipc-1-1  
accepting  
    connections ipc-4-8, ipc-5-13  
    internet domain stream connections ipc-5-11  
    service requests ipc-4-18  
    UNIX domain stream connections ipc-5-17  
access  
    files user-2-2  
    permission user-2-2  
access rights  
    files ipc-6-21  
    passing ipc-6-21  
accessing remote machines smg-8-6  
adb ipc-1-2  
address (A) resource record smg-9-10  
address class  
    choosing smg-3-7  
    defined smg-3-1

address resolution  
 enabling arp smg-4-1  
 host table lookup method smg-3-9  
 HYPERchannel, using *hyroute* smg-5-8  
 internet to Ethernet addresses smg-4-4  
 internet to HYPERchannel addresses smg-5-5  
 internet to UltraNet addresses smg-6-4  
 methods smg-3-9  
 name server method smg-3-9  
 UltraNet, using *unetcf madd* smg-6-4  
 using arp smg-4-4

Address Resolution Protocol (ARP)  
 see *arp*

address space smg-3-1

address structure  
 affect on routing smg-3-8  
 choosing smg-3-6 to smg-3-8  
 HYPERchannel smg-5-5  
 UltraNet smg-6-4

AF\_INET domain, see *internet domain*

AF\_UNIX domain, see *UNIX domain*

aliases  
 for canonical names smg-9-11  
 for host names smg-3-5, smg-3-10, smg-8-6,  
 smg-9-28  
 for multihomed hosts smg-3-5  
 for network names smg-3-12  
 for service names smg-8-1  
 for UltraNet hosts smg-6-3  
 for user names smg-9-12

aliases, host name user-2-1, user-2-2

anonymous ftp account smg-6-9, smg-8-7 to  
 smg-8-8

append, ftp command user-4-9

appending remote files user-4-9

arp  
 enabling with *ifconfig* smg-4-1  
 trailers option smg-4-2  
 using smg-4-4, smg-A-4

ASCII transfer type, ftp user-4-8

associations, socket ipc-4-4, ipc-5-5

asynchronous I/O using user processes,  
 implementation via shared memory ipc-3-9

authority, name server, defined smg-9-1

---

## B

bcmp, use with sockets ipc-4-14

bcopy, use with sockets ipc-4-14

Berkeley Internet Name Domain server, see *BIND*,  
*name server*

bidirectional pipes  
 description ipc-1-2  
 limitations ipc-4-1  
 using ipc-2-6 to ipc-2-8

binary transfer type, ftp user-4-8

BIND smg-9-1 to smg-9-28, user-2-1  
 for host name resolution smg-3-9  
 user mailing list smg-3-6  
 see also *name server*

bind ipc-1-1  
 command syntax ipc-4-4  
 relevant man pages ipc-4-9  
 use with connectionless sockets ipc-6-2  
 used with port number ipc-5-8

binding  
 internet domain sockets ipc-4-6  
 names to sockets ipc-4-2, ipc-4-4  
 UNIX domain sockets ipc-4-5

BITNET, registration smg-3-6, smg-9-18

boot file  
 name server smg-9-6  
 see also *named.boot file*

boot-time parameters smg-2-7 to smg-2-8, smg-7-6  
 gateway smg-2-7, smg-7-6  
 ipforwarding smg-2-7, smg-7-6  
 ipsendredirects smg-2-7, smg-7-6  
 subnetsarelocal smg-2-8  
 udpcksum smg-2-8  
 viop\_enet\_proc smg-2-8

bridges smg-7-1, smg-7-2

broadcast addresses smg-3-4, smg-4-2, smg-4-3,  
 smg-6-4

broadcast packets ipc-6-17

broadcasts  
 datagram-based ipc-6-3  
 sending ipc-6-17  
 status information ipc-6-3  
 use by *rwho* ipc-6-3  
 use in routing ipc-6-4  
 use with connectionless servers ipc-6-3

byte-handling routines  
 bcmp ipc-4-14  
 bcopy ipc-4-14  
 bzero ipc-4-14  
 htonl ipc-4-14  
 htons ipc-4-14, ipc-5-8  
 ntohl ipc-4-14  
 ntohs ipc-4-14  
 summarized ipc-4-14  
 use with datagrams ipc-5-8

bzero, use with sockets ipc-4-14

---

## C

C library smg-9-18

cache command, name server smg-9-6

caching servers smg-9-3

caching-only server, see *name server*

canonical name (CNAME) resource  
 record smg-9-11

CCU smg-2-1, smg-2-2

- Channel Control Unit (CCU) smg-2-1, smg-2-2
- checking status of remote machines user-3-8
- checksums smg-2-8, smg-11-9
- chroot command smg-8-7
- client process smg-8-3
- client/server applications, examples ipc-4-16
- client/server model ipc-4-15
- clients ipc-4-18
- close ipc-1-1, ipc-4-9
- command list
  - ftp user-4-7
  - telnet user-4-3
  - tftp user-4-13
- communication domains, see *domains*
- communication styles
  - datagram ipc-5-1
  - defined ipc-5-1
  - performance considerations ipc-5-2
  - stream ipc-5-1
- compiling on remote machines user-3-7
- connect
  - initiating connections ipc-4-6
  - programming example ipc-4-6
  - relevant man pages ipc-4-9
  - use ipc-1-1
  - use with connectionless sockets ipc-6-2
  - use with datagram sockets ipc-6-2
  - use with stream sockets ipc-5-9
  - used with port numbers ipc-5-8
- connectionless servers
  - broadcasts ipc-6-3
  - description ipc-6-3
  - ruptime ipc-6-3
  - rwho ipc-6-3
  - rwhod ipc-6-3
- connections
  - errors returned ipc-4-7
  - in internet domain, example ipc-4-6
  - in UNIX domain, example ipc-4-6
  - initiating ipc-4-6
- contact command ipc-A-1
- contact utility smg-B-1 to smg-B-7, user-B-1 to user-B-7
  - .contact file, creating ipc-A-6
  - aborting reports ipc-A-6
  - dead.report file ipc-A-6
  - ending a response ipc-A-6
  - suspending reports ipc-A-6
  - using ipc-A-3, ipc-A-6
- controllers, network smg-2-3
- controlling network access
  - ./rhosts file user-2-2
  - hosts.equiv file user-2-2
  - passwords user-2-2
  - using .rhosts file user-2-2
- CONVEX Internet Services, description user-1-2

- copying files
  - using ftp user-4-8
  - using rcp user-3-6
  - using shared memory ipc-3-4
  - using tftp user-4-15
- csd ipc-1-2
- CSNET Coordination and Information Center (CIC), see *CSNET*
- CSNET, registration smg-3-6, smg-9-18

---

## D

- daemonlog file smg-9-20
- daemons
  - networking user-1-1
  - tftp user-4-13
- DARPA Internet user-1-1, user-1-2, smg-3-6, smg-9-18, smg-A-4, smg-A-8, smg-A-12
- datagram sockets
  - creating ipc-4-3
  - defined ipc-1-3, ipc-4-2
  - explained ipc-5-2
  - internet domain ipc-5-5
  - receiving in UNIX domain ipc-5-3
  - sending in UNIX domain ipc-5-4
  - UNIX domain, programming examples ipc-5-3 to ipc-5-4
- datagrams
  - addressing ipc-6-2
  - use in broadcasts ipc-6-17
- DDN Network Information Center (NIC)
  - master database smg-3-15, smg-A-4, smg-A-8
  - registration smg-3-6, smg-3-10
- debugging, socket level smg-11-10 to smg-11-11
- Defense Advanced Research Projects Agency, see *DARPA Internet*
- DESTDIR, name server definition smg-9-20
- device unit description smg-2-4
- device unit numbers smg-2-4
- diagnostics smg-1-1
- directories
  - changing local user-4-10
  - changing remote user-4-10
  - creating remote user-4-10
  - deleting remote user-4-9
  - distributing user-3-11
  - listing remote user-4-10, user-4-11
  - transferring with ftp user-4-9
- directory, name server command smg-9-5
- discarding sockets ipc-4-9
- distributed applications, constructing with sockets ipc-4-15
- domain name pointer (PTR) resource record smg-9-11
- domain names smg-9-1
- DOMAIN, name server definition smg-9-20

domains ipc-5-1  
  AF\_INET, see *internet domain*  
  AF\_UNIX, see *UNIX domain*  
  defined ipc-1-3, ipc-4-2  
  internet ipc-5-1  
    datagrams ipc-5-5  
    description ipc-5-1  
  supported by ConvexOS ipc-4-2  
  supported by sockets ipc-4-3  
  UNIX ipc-5-1  
    datagrams ipc-5-3  
    description ipc-5-1  
  used with socketpairs ipc-2-6  
domains, name server smg-9-1, smg-9-2  
dot notation addresses user-2-1, smg-3-3, smg-3-7  
dup ipc-1-1  
  and piped I/O ipc-2-4  
  example ipc-2-5  
dup2 ipc-1-1  
  and piped I/O ipc-2-4  
  example ipc-2-5

---

## E

ECONNREFUSED error ipc-4-7  
EHOSTDOWN error ipc-4-7  
EHOSTUNREACH error ipc-4-7  
EINVAL, shared memory error message ipc-3-3  
EISCONN error ipc-4-7  
ending  
  ftp session user-4-12  
  remote login session user-3-1  
  rlogin session user-3-1  
  telnet session user-4-5  
  tftp session user-4-17  
ENETDOWN error ipc-4-7  
ENETUNREACH error ipc-4-7  
ENOBUFS, socket error ipc-6-21  
errno ipc-3-3, ipc-6-2, ipc-6-7  
error messages  
  EINVAL ipc-3-3  
  ftp user-4-6  
  interpreting user-1-1  
  on failed connection attempt ipc-4-7  
  received by protocol ipc-5-1  
  returned by accept ipc-4-18  
  returned by connect ipc-4-6  
  returned by listen ipc-5-14  
  returned by mmap ipc-3-3  
  returned by select ipc-6-2, ipc-6-7  
  returned by send ipc-6-2  
  rlogin user-3-5  
  tftp user-4-15, user-4-16  
  when using datagrams ipc-6-2  
  with non-blocking sockets ipc-6-11

Ethernet interface user-1-2  
  /ioconfig file entries smg-2-5  
  controller types smg-2-3  
  device unit type smg-2-4  
  diagnostics smg-1-1  
  host naming conventions smg-3-5  
  troubleshooting smg-4-6  
ETIMEDOUT error ipc-4-7  
EWOULDBLOCK socket error ipc-6-10, ipc-6-11  
ex unit type smg-2-4  
executable files, transferring with ftp user-4-8  
executing commands on remote machines user-3-7

---

## F

fcntl, use in marking non-blocking  
  sockets ipc-6-12  
FD\_CLR macro, use with select ipc-6-6  
FD\_ISSET macro, use with select ipc-6-7  
FD\_SET macro, use with select ipc-6-6  
FD\_ZERO macro, use with select ipc-6-6  
file descriptors  
  interaction with pipe ipc-2-2  
  passing ipc-6-21  
File Transfer Protocol, see *ftp command*  
file transfers  
  using ftp user-4-8 to user-4-9  
  using tftp user-4-15 to user-4-16  
finding version numbers ipc-A-2  
firmware, loading UltraNet smg-6-10  
ftp command  
  access requirements user-4-6  
  append user-4-9  
  command list user-4-7  
  command summary user-A-1 to user-A-3  
  configuring anonymous ftp account smg-8-7  
    to smg-8-8  
  ending a remote session user-4-12  
  errors user-4-6  
  get user-4-8  
  help user-4-7  
  mget user-4-8, user-4-9  
  prompt user-4-9  
  put user-4-8  
  remote shell user-4-6  
  remotehelp user-4-7  
  remotestatus user-4-7  
  retrieving remote files user-4-8  
  running user-4-6  
  status user-4-8  
  transferring files from remote machines user-4-8  
  type user-4-8  
  use in debugging smg-11-10  
  using user-4-6 to user-4-12  
  using to test named smg-9-21  
  with anonymous ftp commands smg-A-2

ftp user smg-8-7  
ftpd smg-A-2  
ftpusers file smg-8-8, smg-A-2  
fttruncate, use with shared memory ipc-3-6  
fully-qualified domain names smg-9-1, smg-9-2

---

## G

gateway, boot-time parameter smg-2-7, smg-7-6  
gateways smg-3-8, smg-7-1 to smg-7-2, smg-7-5,  
smg-A-3  
gateways file smg-3-15, smg-7-3, smg-A-3  
gethostbyaddr ipc-4-10  
gethostbyname ipc-4-10, ipc-5-8  
gethostent ipc-1-1, ipc-4-9  
gethostname ipc-6-4  
getnetbyname ipc-4-11  
getnetbynumber ipc-4-11  
getnetent ipc-4-11  
getpeername ipc-6-16  
getprotobyname ipc-4-3, ipc-4-11  
getprotobynumber ipc-4-11  
getprotoent ipc-1-1, ipc-4-9, ipc-4-11  
getpty ipc-6-14  
getservbyname ipc-4-5, ipc-4-11, ipc-4-17  
getservbyport ipc-4-11  
getservent ipc-1-1, ipc-4-9  
getsockname ipc-5-8  
getsockopt ipc-1-1, ipc-6-20  
gettable command smg-3-15  
getting help  
    with ftp user-4-7  
    with telnet user-4-2  
    with tftp user-4-13  
group file smg-A-10  
groups, network smg-A-5, smg-A-7

---

## H

help, ftp command user-4-7  
host addresses smg-3-1  
    see also *internet addresses*  
host addresses, defined user-2-1  
host database  
    creating smg-3-9 to smg-3-16  
    defined user-2-1  
    maintained by name server smg-9-1  
    see also *host names, internet addresses*  
host information (HINFO) resource  
    record smg-9-10  
host name to address mapping ipc-4-10

host names  
    aliases user-2-1, user-2-2, smg-3-5, smg-3-10  
    choosing smg-3-6  
    conventions smg-3-11, smg-6-3  
    database smg-A-4  
    defined user-2-1, smg-3-1  
    HYPERchannel interface smg-5-5  
    mapping to internet addresses smg-3-9  
    naming conventions smg-3-5, smg-6-3  
    official user-2-2  
    resolving smg-3-9  
    UltraNet interface smg-6-3  
host number smg-3-1  
HOSTADDR, name server definition smg-9-20  
hostent structure ipc-4-10  
hostname command user-3-1, user-A-3  
HOSTNAME, name server definition smg-9-20  
hosts file ipc-4-10  
    description user-2-1, smg-A-4  
    example user-2-1  
    modifying smg-3-9  
    regenerating smg-3-15  
    used with SLIP smg-10-1  
hosts.equiv file smg-8-6, smg-A-5, smg-A-10  
controlling network access user-2-2  
    description user-2-2  
    example user-2-2  
    used with rcp user-3-6  
    used with rlogin user-3-1  
    used with rsh user-3-7  
HOSTSRC, name server definition smg-9-20  
htable command smg-3-15  
htonl ipc-4-14  
htons ipc-4-14, ipc-5-8  
hv device prefix smg-5-2  
hy unit type smg-2-4  
HYP-001 unit type smg-2-4  
HYPERchannel device driver  
    /ioconfig file entry smg-2-6  
    HYP-001 unit type smg-2-4

## HYPERchannel interface user-1-2

- /ioconfig file entries smg-2-6, smg-5-3
- configuring smg-5-1 to smg-5-9
- configuring software smg-5-5 to smg-5-9
- configuring VMEbus controller smg-5-2
- hardware address structure smg-5-5
- hardware board strappings smg-5-1
- hardware installation smg-5-1 to smg-5-4
- host names smg-5-5
- hy unit type smg-2-4
- hyroute command smg-5-5
- ifconfig command smg-5-2
- installing hardware smg-5-1 to smg-5-4
- setting adapter address smg-5-1
- setting timeout value smg-5-1
- setting unit value smg-5-1
- solving configuration problems smg-5-7
- testing hardware configuration smg-5-4
- testing software configuration
  - using netstat smg-5-4
  - using ping smg-5-7
- troubleshooting smg-5-7
- verifying ifconfig entries smg-5-7
- VMEbus switch settings smg-5-2
- hyroute command smg-5-5

---

## I/O controller types smg-2-3

- ifconfig command
  - configuring Ethernet interface smg-4-1
  - configuring HYPERchannel interface smg-5-2, smg-5-7
  - configuring loopback interface smg-3-13
  - setting broadcast address smg-4-2, smg-4-3
  - setting subnet mask smg-3-8, smg-3-13, smg-3-14, smg-4-2, smg-4-3
  - trailers option smg-4-2
  - verifying configuration smg-4-2, smg-4-6
- IKON 10077-NSC Multibus HYPERchannel interface smg-5-1
- IKON 10090 VMEbus HYPERchannel interface smg-5-1, smg-5-3
- inetd ipc-4-9, ipc-4-15, ipc-6-16
- inetd, configuring smg-8-3 to smg-8-5, smg-A-6
- inetd.conf file
  - description smg-8-3, smg-A-6
  - editing for UltraNet smg-6-8
  - example smg-8-4
  - use in debugging smg-11-10
- info command smg-B-2, user-B-2
- interface types smg-2-2

## internet addresses

- address resolution smg-3-9
- as packet destination smg-7-1
- assigning smg-3-9
- broadcast smg-3-4, smg-4-2
- choosing smg-3-6
- description smg-3-1 to smg-3-5
- dot notation smg-3-3, user-2-1
- for multihomed hosts smg-3-5
- HYPERchannel smg-5-5
- internal representation smg-3-1 to smg-3-2
- loopback interface smg-3-13
- network smg-3-4
  - see also *network addresses*
- official smg-3-6, smg-3-12
- port number ipc-5-1
- registration smg-3-6
- reserved smg-3-4
- resolving with arp smg-4-4
- specifying for sockets ipc-5-8
- structure ipc-5-5
- subnets
  - creating smg-3-7 to smg-3-8
  - defining smg-4-3
  - example smg-3-14
  - subnet mask smg-4-2
- UltraNet smg-6-1, smg-6-3
- Internet Control Message Protocol (ICMP) smg-2-7, smg-11-9
- internet domain ipc-5-1
  - addresses ipc-5-1
  - datagrams used in ipc-5-5
  - defined ipc-4-2, ipc-4-3
  - description ipc-5-1
  - introduced ipc-1-3
  - socket call example ipc-4-3
  - socket names ipc-5-5
- internet network smg-3-1, smg-7-1, smg-8-1
- internet superserver daemon, see *inetd*
- interrupt-driven sockets ipc-6-12
- IP network protocol smg-11-9
- IPC facilities
  - interactions with operating system ipc-1-1
  - introduction ipc-1-1
  - table ipc-1-1
- IPC programming, introduction ipc-1-1
- ipforwarding, boot-time parameter smg-2-7, smg-7-6
- ipsendredirects, boot-time parameter smg-2-7, smg-7-6

---

## L

### LAN

- defined user-1-1
- model user-1-2
- user access user-1-2
- libc.a ipc-4-3, smg-9-18
- library routines used with sockets ipc-4-10
- libulsock.a ipc-4-3
- LINEMODE, telnet option user-4-4
- listen ipc-4-7, ipc-4-9, ipc-5-14
- local area network, see LAN
- localgateways file smg-3-15
- localhost smg-3-13
- localhosts file smg-3-15
- localnetworks file smg-3-15
- LOG\_DAEMON smg-9-20
- LOG\_DEBUG smg-9-20
- login names user-3-4
- login shells, with ftp command user-4-6
- logins, remote smg-8-6
- logout command user-3-1
- loopback interface smg-3-13

---

## M

- machine names on the network user-2-1
- mail exchanger (MX) resource record smg-9-13
- mail group member (MG) resource record smg-9-13
- mail rename (MR) resource record smg-9-12
- mailbox (MB) resource record smg-9-12
- mailbox information (MINFO) resource record smg-9-12
- Makefile, for building name server smg-9-19
- malloc ipc-3-3
- mapping
  - description ipc-4-10
  - host names to network addresses ipc-4-10
  - host names to numbers ipc-4-11
  - network names to numbers ipc-4-11
  - protocol names ipc-4-11
  - service names ipc-4-11
- master server, see *name server*
- Maximum Transmission Unit (MTU)
  - displaying smg-11-4
  - setting smg-5-5
- mbufs, displaying smg-11-6
- mclear ipc-3-6
- mget, ftp command user-4-8, user-4-9
- mknod ipc-2-9
- mmap ipc-1-1, ipc-3-3
- mput, ftp command user-4-8
- mset ipc-3-6
- MSG\_PEEK, use with out-of-bound data ipc-6-9
- msleep ipc-3-6

## MTU

- displaying smg-11-4
- setting smg-5-5
- multihomed hosts smg-3-5, smg-6-3
- munmap ipc-1-1, ipc-3-6
- mwakeup ipc-3-6

---

## N

- name resolution, see *address resolution*
- name server user-2-2, smg-9-1 to smg-9-28
  - \$INCLUDE directive smg-9-8
  - \$ORIGIN directive smg-9-8
  - adding hosts to database smg-9-28
  - benefits of using smg-3-9
  - boot file
    - cache command smg-9-6
    - description smg-9-4
    - directory command smg-9-5
    - example smg-9-5
    - primary command smg-9-5
    - secondary command smg-9-6
    - sortlist command smg-9-6
  - caching servers smg-9-3
  - caching-only server
    - configuring smg-9-26
    - defined smg-9-3
  - control files smg-9-4 to smg-9-7
  - daemon smg-9-3
  - data files smg-9-8 to smg-9-17, smg-9-20
  - DESTDIR definition smg-9-20
  - DOMAIN definition smg-9-20
  - domains smg-9-1 to smg-9-2
  - file summary smg-9-4
  - for host name resolution smg-3-9
  - HOSTADDR definition smg-9-20
  - HOSTNAME definition smg-9-20
  - HOSTSRC definition smg-9-20
  - Makefile smg-9-19
  - named smg-9-3
  - primary master server
    - configuring smg-9-19 to smg-9-24
    - description smg-9-3
  - remote server smg-9-3
  - resolv.conf file smg-9-27
  - resolver routines smg-9-3
  - resolving-only server smg-9-3
    - configuring smg-9-27
    - description smg-9-3
  - root directory smg-9-5
  - root.cache file smg-9-17
  - running smg-9-20
  - secondary master server
    - configuring smg-9-25 to smg-9-26

- description smg-9-3
- server types smg-9-3
- software components smg-9-3
- starting from rc.local script smg-9-21
- types smg-9-3
- use\_nameserver file smg-9-7, smg-9-18, smg-9-21, smg-9-26, smg-9-27
- user mailing list smg-9-18
- name server (NS) resource record smg-9-10
- name server definitions
  - DOMAIN smg-9-20
  - HOSTSRC smg-9-20
  - DESTDIR smg-9-20
  - HOSTADDR smg-9-20
  - HOSTNAME smg-9-20
  - ROOT smg-9-20
- name space ipc-4-1
- named, see *name server*, *BIND*
- named.boot file
  - caching-only server example smg-9-26
  - creating smg-9-20
  - description smg-9-4 to smg-9-6
  - primary master server example smg-9-23
  - secondary master server example smg-9-25
- named.hosts file
  - creating smg-9-20
  - description smg-9-13 to smg-9-14
  - example smg-9-14, smg-9-23
  - modifying smg-9-28
- named.local file
  - creating smg-9-20
  - example smg-9-15
  - primary master server example smg-9-24
  - secondary master server example smg-9-25
- named.pid file smg-9-6
- named.reload script smg-9-6, smg-9-20, smg-9-28
- named.restart script smg-9-6, smg-9-7
- named.rev file
  - creating smg-9-20
  - description smg-9-15 to smg-9-16
  - modifying smg-9-28
  - primary master server example smg-9-24
- naming conventions
  - Ethernet smg-3-11
  - multihomed hosts smg-3-5
  - UltraNet smg-6-3
- native UltraNet interface
  - adding adapters smg-6-5
  - defined smg-6-1
  - host names smg-6-3
  - mapping addresses smg-6-4
  - routing smg-6-6, smg-6-7
  - testing smg-6-12
- NB400 HYPERchannel Adapter
  - assigning unit value smg-5-6
  - setting timeout value smg-5-1
  - setting unit value smg-5-1
  - solving configuration problems smg-5-7
- netdb.h header file ipc-4-10
- netent ipc-4-11
- netgroup file user-2-2, smg-8-6, smg-A-7, smg-A-10, smg-A-11
- netinet/in.h structure ipc-5-5, ipc-6-17
- netmask smg-3-8, smg-4-2
- netstat command
  - determining network status smg-11-3
  - displaying autoconfigured interfaces smg-11-4
  - displaying data for selected protocols smg-11-7
  - displaying data per protocol smg-11-8
  - displaying memory management statistics smg-11-6
  - displaying MTUs smg-11-4
  - displaying process control blocks smg-11-11
  - displaying status of all sockets smg-11-5
  - numerical address format smg-11-6
  - testing Ethernet configuration smg-4-6
  - testing HYPERchannel configuration smg-5-4
  - testing UltraNet configuration smg-6-12
  - using smg-11-4 to smg-11-9
  - verifying routes smg-7-6
- network
  - accessing user-2-2, smg-8-6 to smg-8-8
  - checking status of user-3-8
  - checking users user-3-9
  - classes smg-3-13
  - daemons user-1-1
  - host names user-2-1
  - network access user-2-1, user-2-2
  - .rhosts file user-2-2
  - hosts.equiv file user-2-2
  - passwords user-1-2, user-2-2
  - using .rhosts file user-2-3
  - network addresses smg-3-1, smg-3-4, smg-3-10
    - see also *internet addresses*, *host addresses*
  - network daemons, starting smg-8-3, smg-8-5
  - Network File System (NFS) ipc-1-1, user-2-1, user-2-2
  - Network File System (NFS), see *NFS*
  - network groups user-2-2, smg-A-5, smg-A-7
  - network hardware smg-2-1
    - Ethernet interface user-1-2
    - HYPERchannel interface user-1-2
    - UltraNet interface user-1-2
  - Network Information Center (NIC), see *DDN Network Information Center (NIC)*

- network interfaces
  - controller types smg-2-3
  - device unit descriptions smg-2-4
  - Ethernet smg-4-1
  - HYPERchannel smg-5-1
  - naming conventions smg-3-5
  - types smg-2-2
  - UltraNet smg-6-1
- network names smg-3-12
- network number smg-3-1, smg-3-10
- network performance, boot-time
  - parameters smg-2-7
- network registration agencies
  - BITNET smg-3-6, smg-9-18
  - CSNET smg-3-6, smg-9-18
  - DARPA Internet smg-3-6, smg-9-18
  - NIC smg-9-18
- network services
  - configuring smg-8-1 to smg-8-5
  - controlling access to smg-8-6
  - testing with telnet smg-8-5
- network software
  - customizing boot-time parameters smg-2-7
  - description smg-1-1 to smg-1-2
  - HYPERchannel smg-5-5
  - UltraNet smg-6-1
- Network Systems Corporation A400 Adapter
  - see *A400 HYPERchannel Adapter*
- networks file smg-11-3
  - description smg-A-8
  - HYPERchannel entries smg-5-6
  - modifying smg-3-12
  - regenerating smg-3-15
  - UltraNet entries smg-6-3
- NFS smg-8-3, smg-8-4, smg-8-6, smg-A-5, smg-A-9, smg-A-11
- NIC, see *DDN Network Information Center*
- non-blocking sockets ipc-6-11
- NSC NB400 HYPERchannel Adapter
  - see *NB400 HYPERchannel Adapter*
- nslookup command smg-9-21
- ntohl ipc-4-14
- ntohs ipc-4-14

## O

- obtaining remote help information user-4-7
- official host names user-2-2
- open ipc-2-9
- operating system
  - implementation of pipes ipc-2-1
  - interface to IPC facilities ipc-1-1
- options, socket ipc-6-20
- out-of-band data ipc-4-8, ipc-5-16, ipc-6-6, ipc-6-9, ipc-6-21

## P

- packet routing smg-7-3
- packet-switching computers smg-7-1
- parameters, boot-time smg-2-7
- passwd file smg-8-7, smg-A-10
- passwords
  - for remote access smg-8-6, smg-A-5, smg-A-10
  - root user-2-2
  - used with anonymous ftp account smg-8-7
  - user access user-1-2, user-2-2, user-2-3, user-3-1
  - user validation user-2-2
  - when using ftp user-4-6
  - when using rcp user-3-6
  - when using rsh user-3-7
  - when using tftp user-4-13
- pattach command ipc-1-2
- PIDFILE parameter smg-9-6
- ping
  - sample output smg-11-2
  - testing HYPERchannel interface smg-5-7
  - testing name server smg-9-21
  - testing network configuration smg-11-1
  - troubleshooting with smg-11-3, smg-11-5
- pipes
  - and child/parent communication ipc-2-3
  - as examples of stream communication ipc-2-4
  - bidirectional ipc-1-2, ipc-2-6 to ipc-2-8
  - defined ipc-1-2
  - how shell sets up ipc-2-1
  - interaction with file descriptors ipc-2-2
  - interaction with user code ipc-2-2
  - limitations ipc-4-1
  - named ipc-2-9 to ipc-2-10
  - operating system interface ipc-2-1
  - sample program ipc-2-2
  - simple ipc-2-1 to ipc-2-5
  - using ipc-2-1 to ipc-2-10
  - using dup for I/O ipc-2-4
- pipng, defined ipc-2-1
- point-to-point connection, via SLIP smg-10-1
- port number used in internet domain ipc-5-8
- portmap daemon smg-8-3
- primary master server, see *name server*
- primary, name server command smg-9-5
- problems
  - assistance with ipc-A-1, smg-B-1, user-B-1
  - in documentation ipc-A-4, smg-B-4, user-B-4
  - priority of ipc-A-4, smg-B-4, user-B-4
  - reporting ipc-A-1, smg-B-1, user-B-1
- process control blocks, displaying smg-11-11
- process tracing, defined ipc-1-2
- program version number, finding ipc-A-2, smg-B-2, user-B-2
- prompt, ftp command user-4-9
- protocol name mapping ipc-4-11

- protocols ipc-4-4, ipc-5-2
- protocols file smg-8-3
- protocol structure ipc-4-11
- ps command smg-11-3
- pseudoterminals
  - obtaining master/slave pairs ipc-6-14
  - programming example ipc-6-15
  - use with sockets ipc-6-14
- put
  - ftp command user-4-8
  - tftp command user-4-16

---

## R

- raw sockets ipc-1-3, ipc-4-2
- rc script smg-6-10
- rc.local script
  - adding static routes smg-7-4, smg-7-5
  - configuring HYPERchannel interface smg-5-7
  - configuring loopback interface smg-3-13
  - configuring UltraNet interface smg-6-10
  - defining default routes smg-7-5
  - example smg-4-5
  - running ifconfig from smg-4-5
  - setting subnet mask smg-3-14
  - starting name server smg-9-21, smg-9-26, smg-9-27
  - starting routed smg-7-3
  - starting unetd smg-6-8
  - troubleshooting smg-11-3
  - unetcf madd commands smg-6-4
- rc.ultra script smg-6-10
- rcp command
  - summary user-A-3 to user-A-4
  - using user-3-6 to user-3-7
- read ipc-1-1, ipc-2-9, ipc-4-8, ipc-4-9
  - use with mapped files ipc-3-4
  - use with shared memory ipc-3-4
  - used with named pipes ipc-2-9
- recv ipc-4-8, ipc-4-9
- recvfrom, use with connectionless sockets ipc-6-2
- remote access
  - files user-2-2
  - using ftp user-4-6
  - using rlogin user-3-1
  - using rsh user-3-7
  - using telnet user-4-1
  - using tftp user-4-13
- remote command execution user-3-7
- remote files, appending user-4-9

- remote logins user-2-2, smg-8-6
  - aborting user-3-2
  - controlling access user-2-2
  - suspending user-3-3
  - terminating user-3-1
  - user validation user-2-2
    - with no home directory user-3-4
- remotehelp, ftp command user-4-7
- remotestatus, ftp command user-4-7
- reporting problems ipc-A-1, smg-B-1, user-B-1
- Requests for Comments (RFCs) smg-9-1
- reserved addresses smg-3-4
- resolv.conf file smg-9-20, smg-9-27
- resolver, name server smg-9-3
- resolving-only server, see *name server*
- resource records
  - address (A) smg-9-10
  - canonical name (CNAME) smg-9-11
  - domain name pointer (PTR) smg-9-11
  - host information (HINFO) smg-9-10
  - mail exchanger (MX) smg-9-13
  - mail group member (MG) smg-9-13
  - mail rename (MR) smg-9-12
  - mailbox (MB) smg-9-12
  - mailbox information (MINFO) smg-9-12
  - name server (NS) smg-9-10
  - standard format smg-9-8
  - start of authority (SOA) smg-9-9
  - types smg-9-9
  - well-known services (WKS) smg-9-11
- rlogin command smg-8-6
  - aborting user-3-2
  - ending a remote session user-3-1
  - error messages user-3-5
  - summary user-A-3
  - suspending user-3-3
  - user validation user-2-2
    - using user-3-1 to user-3-5
    - using different user names user-3-4
    - versus using telnet user-4-1
      - with no home directory user-3-4
- rm, use with UNIX domain datagrams ipc-5-4
- root account
  - controlling access smg-8-6, user-2-2
  - login validation user-2-2
- root password user-2-2
- ROOT, name server definition smg-9-20
- root.cache file smg-9-17
- route command
  - creating static routes smg-7-4
  - defining wildcard routes smg-7-5
- routed smg-7-3, smg-A-3

- routes
  - default smg-7-5
  - defined smg-7-1
  - displaying for UltraNet smg-6-7
  - static smg-7-4
  - verifying with netstat smg-7-6
  - wildcard smg-7-5
- routing
  - bridges smg-7-1, smg-7-2
  - creating static routes smg-7-4
  - defined smg-7-1
  - description smg-7-3
  - gateways smg-7-1
  - packet-switching computers smg-7-1
  - UltraNet smg-6-6
  - using default routes smg-7-5
- routing daemon smg-7-3, smg-A-3
- routing-redirect messages smg-7-5
- rpc daemons smg-8-3
- rpc file smg-8-3
- rsh command user-3-7, user-A-4
- ruptime
  - as example of connectionless server ipc-6-3
- ruptime command user-3-8, user-A-4
- rwho command user-3-9, user-A-4
- rwho, as example of connectionless server ipc-6-3
- rwhod smg-11-9
- rwhod, as example of connectionless server ipc-6-3

## S

- secondary master server, see *name server*
- secondary, name server command smg-9-6
- seek ipc-3-3
- select ipc-5-14
  - use in multiplexed I/O ipc-6-6
  - use with connectionless sockets ipc-6-2
  - use with inetd ipc-6-16
  - use with out-of-bound data ipc-6-9
  - values returned by ipc-6-7
- send ipc-4-8, ipc-4-9
  - use with connectionless sockets ipc-6-2
  - used on unbound socket ipc-5-8
- sendto, use with connectionless sockets ipc-6-2
- sequential I/O, using shared memory to implement ipc-3-4
- Serial Line Internet Protocol, see *SLIP*
- servent structure ipc-4-11
- server process smg-8-3
- servers ipc-4-15
- service definitions, used with socket servers ipc-4-17
- service mapping, sockets ipc-4-11

- services file ipc-4-11
  - description smg-8-1 to smg-8-2, smg-A-12
  - inetd.conf file entries smg-8-3
  - name server smg-9-3
  - standard port numbers smg-9-18, smg-A-6
- setsockopt ipc-1-1, ipc-6-20
- Share smg-9-20
- shared memory
  - advantages of ipc-3-1
  - arguments used with mmap ipc-3-3
  - description ipc-1-3
  - error messages returned by mmap ipc-3-3
  - programming example ipc-3-2
  - stsem calls ipc-3-1
  - unmapped shared memory segments ipc-3-6
  - use in asynchronous I/O using user processes ipc-3-9
  - use in copying files ipc-3-4
  - use in mapping kernel and physical memory ipc-3-21
  - use in sequential I/O ipc-3-4
  - use in stressing virtual memory system ipc-3-11
  - use with counting semaphores ipc-3-6
  - use with multiple processes ipc-3-6
  - using ipc-3-1 to ipc-3-21
- shutdown ipc-4-9
- SIGCHLD signal ipc-6-13
- SIGIO signal ipc-6-13
  - use with interrupt-driven socket I/O ipc-6-12
- signal, terminating stream communication ipc-5-9
- signals, defined ipc-1-2
- SIGPIPE signal, after connection is closed ipc-5-9
- SIGURG signal ipc-6-13
  - use with interrupt-driven socket I/O ipc-6-12
  - use with out-of-bound data ipc-6-9
- slattach command smg-10-2
- SLIP
  - checksumming smg-11-9
  - using smg-10-1 to smg-10-2
- SO\_BROADCAST socket option ipc-6-20
- SO\_DONTROUTE socket option ipc-6-20
- SO\_ERROR socket option ipc-6-20
- SO\_KEEPALIVE socket option ipc-6-21
- SO\_OOBINLINE socket option ipc-6-21
- SO\_RCVBUF socket option ipc-6-20
- SO\_REUSEADDR socket option ipc-6-20, ipc-6-21
- SO\_SNDBUF socket option ipc-6-20
- SO\_SNDBUF socket option ipc-6-20
- SO\_TYPE socket option ipc-6-20
- sockaddr\_in structure ipc-4-5
- sockaddr\_un structure ipc-4-5
- socket ipc-6-17
- socket ipc-1-1, ipc-4-3, ipc-4-9
  - examples ipc-5-3, ipc-5-4

- socket servers
  - service definitions used with ipc-4-17
  - use with inetd ipc-4-15
- socketpair
  - ipc-2-8
  - defined ipc-2-6
  - description ipc-1-2
  - introduction ipc-1-1
  - programming example ipc-2-7
- socketpairs
  - domains used with ipc-2-6
  - limitations ipc-4-1
  - using ipc-2-6
- sockets
  - associations ipc-4-4, ipc-5-5
  - binding in internet domain, example ipc-4-6
  - binding in UNIX domain, example ipc-4-5
  - binding names to ipc-4-2, ipc-4-4
  - byte-handling routines ipc-4-14
  - client side ipc-4-18
  - client/server model ipc-4-15
  - communication styles ipc-5-1
  - connectionless ipc-6-2
  - connectionless servers
    - broadcasts used by ipc-6-3
    - description ipc-6-3
  - connections,
    - simultaneous client requests ipc-5-14
  - constructing distributed applications
    - for ipc-4-15
  - creating
    - datagram type ipc-4-3
    - description ipc-4-3
    - internet domain ipc-4-3
    - stream type ipc-4-3
    - UNIX domain example ipc-4-3
  - datagram ipc-5-1
    - explained ipc-5-2
    - programming examples ipc-5-3 to ipc-5-8
    - UNIX domain ipc-5-3
  - datagram sockets
    - defined ipc-1-3
    - using ipc-4-2
  - datagrams in the internet domain ipc-5-5
  - description ipc-1-3, ipc-4-2
  - discarding ipc-4-9
  - domains ipc-5-1
  - errors returned
    - with connectionless sockets ipc-6-2
  - host name to address mapping ipc-4-10
  - initiating connections ipc-4-6
  - internal system implementation ipc-4-2
  - internet addresses
    - specifying ipc-5-8
  - internet domain
    - port numbers ipc-5-8
    - reading datagrams, example ipc-5-6
    - sending datagrams, example ipc-5-7
    - interrupt driven ipc-6-12
    - introduction to using ipc-4-1
    - linking programs with ipc-4-3
    - mapping host names to numbers ipc-4-11
    - miscellaneous routines ipc-4-12
    - non-blocking ipc-6-11, ipc-6-12
    - options ipc-6-20
    - protocol-name mapping ipc-4-11
    - raw, defined ipc-1-3
    - raw sockets ipc-4-2
    - reasons for failure ipc-4-4
    - sending broadcasts ipc-6-17
    - service mapping ipc-4-11
    - setting and retrieving options ipc-6-20
    - specifying attributes ipc-5-2
    - stream ipc-5-1
      - explained ipc-5-1
    - stream sockets
      - defined ipc-1-3
      - using ipc-4-2
    - streams, creating connections ipc-5-9
    - system calls, summarized ipc-4-9
    - transferring data ipc-4-8
    - types ipc-4-2
      - defined ipc-1-3
      - UltraNet ipc-4-3
      - use in passing access rights ipc-6-21
      - use in passing file descriptors ipc-6-21
      - using inetd ipc-6-16
      - using network library routines with ipc-4-10
      - using select to multiplex I/O ipc-6-6
  - sortlist, name server command smg-9-6
  - SPU
    - /mnt/errlog file smg-5-4
    - displaying /ioconfig file smg-2-1
    - running diagnostics on smg-1-1
    - start of authority (SOA) resource record smg-9-9
    - station addresses, UltraNet smg-6-4
    - status
      - ftp command user-4-8
      - telnet command user-4-4
      - tftp command user-4-14
    - status checking
      - using ftp user-4-7
      - using ruptime user-3-8
      - using rwho user-3-9
      - using telnet user-4-4
      - using tftp user-4-14
    - stream communication, pipes as examples
      - of ipc-2-4
    - stream sockets
      - creating ipc-4-3
      - creating connections ipc-5-9
      - defined ipc-1-3, ipc-4-2
      - explained ipc-5-1
      - subdomain smg-9-2

## subnets

- benefits of using smg-3-7, smg-3-8, smg-3-13
- description smg-3-7 to smg-3-8, smg-3-13
- implementing smg-3-13
- netmask smg-3-8
- setting subnet mask smg-3-14
- setting subnet mask smg-3-13, smg-4-2, smg-4-3
- subnet addresses
  - dot notation smg-3-7
  - example smg-3-14
  - illustrated smg-3-7
  - setting subnet mask smg-4-2
  - subnet field smg-3-13
- subnet mask
  - default smg-4-3
  - setting smg-3-8, smg-4-3
- subnet numbers, dot notation smg-3-3
- subnetsarelocal, boot-time parameter smg-2-8
- subnetting a single network interface smg-3-8
- subnetting multiple network interfaces smg-3-8
- used with UltraNet interface smg-3-7
- subnetsarelocal, boot-time parameter smg-2-8
- subnetting, see *subnets*
- subnetworks, see *subnets*
- suspending a remote login user-3-3
- sys/socket.h header file
  - use with send and recv ipc-4-8
  - used with socketpairs ipc-2-6
- sys/types.h header file
  - use with socketpairs ipc-2-6
- sys/un.h structure ipc-5-3
- syslog
  - inetd errors smg-8-3
  - name server errors smg-9-20
- syslog, logging errors ipc-4-17, ipc-4-18
- syslog.conf file, name server errors smg-9-20
- syspic command smg-11-3
- system calls, summarized ipc-1-1
- system security smg-8-7, smg-A-10

## T

- TAC smg-11-13, ipc-A-1, smg-B-1 to smg-B-7
- talk ipc-1-1
- tar files, transferring with ftp user-4-8
- tcp ipc-4-9
- TCP, displaying statistics for smg-11-7, smg-11-9
- TCP/IP network smg-3-1, smg-7-1, smg-8-1
- Technical Assistance Center ipc-A-1
- Technical Assistance Center (TAC) user-B-1 to user-B-7

## telnet command

- command list user-4-3
- ending session user-4-5
- escape sequence user-4-2
- invoking user-4-2
- running user-4-1
- status option user-4-4
- summary user-A-4 to user-A-5
- testing network services smg-8-5
- using user-4-1 to user-4-5
- using LINEMODE user-4-4
- TELNET protocol user-4-1
- terminating a remote session user-3-1
- tftp command
  - access restrictions user-4-13
  - command list user-4-13
  - daemon user-4-16
  - ending remote session user-4-17
  - get user-4-15
  - put user-4-16
  - retrieving remote files user-4-15
  - running user-4-13
  - status user-4-14
  - using user-4-13 to user-4-17
- tftpd user-4-13, user-4-16
- trailers, ifconfig option smg-4-2
- transfer type, using ftp user-4-8
- transferring data with sockets ipc-4-8
- transferring files
  - using ftp user-4-6, user-4-8
  - using rcp user-3-6
  - with tftp user-4-15
- Transmission Control Protocol, see *TCP*
- Trivial File Transfer Protocol, see *tftp*
- troubleshooting smg-11-1 to smg-11-13
  - displaying mbufs smg-11-6
  - Ethernet interface smg-4-6
  - general procedure smg-11-3
  - HYPERchannel interface smg-5-11
  - overview smg-11-1
  - UltraNet interface smg-6-12
  - using ping smg-11-2, smg-11-3, smg-11-5
  - using ps smg-11-3
  - using syspic smg-11-3
  - using trpt smg-11-3
- trpt command
  - sample output smg-11-11
  - socket level debugging smg-11-10, smg-11-11
  - used for troubleshooting smg-11-3
- tsock smg-6-12, smg-11-12, smg-11-13
- type, ftp command user-4-8

## U

- udp ipc-4-9
- udpcksum, boot-time parameter smg-2-8

- UltraNet interface user-1-2
  - /ioconfig file entry smg-2-6
  - adapter group and unit numbers smg-6-4
  - adding adapters smg-6-5
  - adding routes smg-6-6
  - anonymous ftp account smg-6-9
  - configuration task summary smg-6-2
  - configuring smg-6-1 to smg-6-11
  - controller types smg-2-3
  - deleting adapters smg-6-5
  - deleting routes smg-6-7
  - description smg-6-1
  - device unit type smg-2-4
  - displaying adapters smg-6-5
  - displaying routes smg-6-7
  - firmware, loading smg-6-10
  - host names smg-6-1, smg-6-3
  - host naming conventions smg-6-3
  - internet addresses smg-6-3
  - internet interface smg-6-1
  - loading firmware smg-6-2, smg-6-10
  - mapping addresses smg-6-4 to smg-6-5
  - mappings file smg-6-5
  - native interface smg-6-1
  - network daemons smg-6-8
  - network numbers smg-6-3
  - network servers smg-6-8
  - network software smg-6-1
  - performance smg-6-1
  - routing smg-6-6 to smg-6-7, smg-7-1
  - sample networks file smg-6-3
  - servers smg-6-8
  - sockets compatibility library smg-1-1
  - station addresses smg-6-4
  - testing with netstat smg-6-12
  - testing with tsock smg-6-12
  - using default routes smg-6-6
  - using tsock smg-11-12
- UltraNet Socket Compatibility Library ipc-4-3
- UltraNet sockets ipc-4-3
- unet unit type smg-2-4
- unetcf
  - aadd command smg-6-5
  - adel command smg-6-7, smg-11-13
  - adis command smg-6-5
  - madd command smg-6-4
  - mdel command smg-6-5
  - radd command smg-6-6
  - rdel command smg-6-7
  - rdis command smg-6-7
- unetd smg-6-8
- unetd.conf file smg-6-8
- unit numbers smg-2-4
- unit types smg-2-4
- UNIX communication domain ipc-4-2

- UNIX domain
  - defined ipc-2-6
  - described ipc-5-1
  - introduced ipc-1-3
  - pathnames ipc-5-4
  - receiving datagrams ipc-5-3
  - sending datagrams ipc-5-4
  - socket call example ipc-4-3
  - socket names ipc-5-5
- UNIX-to-UNIX Communication Protocols, see UUCP
- unlink, use with UNIX domain datagrams ipc-5-4
- unmapping shared memory segments ipc-3-6
- use\_nameserver file smg-9-7, smg-9-18, smg-9-21, smg-9-22, smg-9-26, smg-9-27
- user access
  - .rhosts file user-2-2
  - hosts.equiv file user-2-2
  - passwords user-1-2
  - remote logins user-2-2
- User Datagram Protocol (UDP) smg-11-9
- UUCP user-1-1, user-1-2, ipc-A-2, user-B-2
- uucp
  - connection, contacting TAC smg-B-2
  - with anonymous ftp account smg-8-7
- uvm32.ult file smg-6-2
- uvmload smg-6-2

---

## V

- vers command ipc-A-2, smg-B-2, user-B-2
- version number, program, finding ipc-A-2, ipc-A-7, smg-B-2, smg-B-7, user-B-2, user-B-7
- viop\_enet\_proc, boot-time parameter smg-2-8

---

## W

- well-known services (WKS) resource
  - record smg-9-11
- whence command ipc-A-2, smg-B-2, user-B-2
- which command smg-B-2, user-B-2
- which command ipc-A-2
- who command smg-8-8
- write ipc-1-1, ipc-4-8, ipc-4-9, ipc-5-1
  - use with named pipes ipc-2-9
  - use with shared memory ipc-3-4
  - used with pipes ipc-2-4

---

## Y

- Yellow Pages (YP) smg-8-6, smg-A-5, smg-A-11, user-2-1, user-2-2

---

## Z

- zones of authority smg-9-1