



CONVEX

qmgr & qmapmgr
Quick Reference

First Edition

CONVEX Computer Corporation
Richardson, Texas USA

CONVEX

qmgr & qmapmgr

Quick Reference

Order No. DSW-187

Copyright 1990 CONVEX Computer Corporation.

All rights reserved.

CONVEX and the CONVEX logo  are registered trademarks of CONVEX Computer Corporation.

Printed in the United States of America.

qmgr

At the **qmgr Mgr:** prompt, enter:

ABort Queue *queuename* [*seconds*]
ADd Alias *alias queuename*
ADd DESTination = (*destination* [...]) *queuename*
ADd DESTination = *destination queuename*
ADd Groups = (*group* [...]) *queuename*
ADd Groups = *group queuename*
ADd Managers *username:option* [...]
ADd Users = (*user* [...]) *queuename*
ADd Users = *user queuename*

CHkpt Request *request_id*
Create Batch_queue *queuename* PRiority =
 priority [PIpeonly] [Run_limit = *run-limit*]
 [Import_dir = *import-option*] [Share_policy
 Fixed = *username*] [Share_policy User]
Create Pipe_queue *queuename* PRiority = *priority*
 Server = (*server*) [Destination = (*destination*
 [,...]) [PIpeonly] [Run_limit = *run-limit*]

DElete Alias *alias*
DElete DESTination = (*destination* [...]) *queuename*
DElete DESTination = *destination queuename*
DElete Groups = (*group* [...]) *queuename*
DElete Groups = *group queuename*
DElete Managers *username: option* [...]
DElete Queue *queuename*
DElete Request *request-id* [...]
DElete Users = (*user* [...]) *queuename*
DElete Users = *user queuename*
DIisable Queue *queuename*

ENable Queue *queuename*

EXit

HElP [*command*]

HOLd Request *request-id* [...]

MODify Request [*attribute*]= *value request-id*[...]

MOVE My_request *request-id* [...] *queuename*

MOVE Queue *queuename1 queuename2*

MOVE Request *request-id* [...] *queuename*

Purge Queue *queuename*

RELease Request *request-id* [...]

REStart Request *request-id* [...]

REsume Request *request-id* [...]

RUn Request *request-id* [...]

SEt ACC_logfile *logfile-name*

SEt ACCOunting = *switch queuename*

SEt ACTivity_id_offset = *offset-value queuename*

SEt AId_mask = *mask-value*

SEt CHEckpoint_directory *checkpoint-directory*

SEt CHKpntable = [*option*] *queuename* {Yes, No, Avail-
able}

SEt COREfile_limit = (*limit*) *queuename*

SEt DATA_limit = (*limit*) *queuename*

SEt DEBUg *level*

SEt DEFault Batch_request Priority *priority*

SEt DEFault Batch_request Queue *queuename*

SEt DEFault DESTination_retry Time *retry-
time*

SEt DEFault DESTination_retry Wait *wait-time*

SEt DEScriptioN = (*description*) *queuename*

SEt DESTination = (*destination* [...]) *queuename*

SEt DESTination = *destination queuename*

SEt Global Per_user Run_limit = *run-limit*
SEt Import_dir *queuename option*
SEt MAIL *userid*
SEt MANagers *username: option [...]*
SEt MAXimum Request_priority *priority queuename*
SEt NICE_value_limit = *nice-value queuename*
SEt NO_Access *queuename*
SEt NO_Default Batch_request Queue
SEt PER_Process Cpu_limit = (*limit*) *queuename*
SEt PER_Process Permfile_limit = (*limit*) *queuename*
SEt PER_User Run_limit = (*run-limit*) *queuename*
SEt Pipe_client = (*client*) *queuename*
SEt Priority = *priority queuename*
SEt Run_limit = *run-limit queuename*
SEt SHAre_strategy FIXed = *username queuename*
SEt SHAre_policy User *queue*
SEt SHell_policy FIXed = (*shell*)
SEt SHell_strategy FRee
SEt SHell_strategy Login
SEt STack_limit = (*limit*) *queuename*
SEt Unrestricted_access *queuename*
SEt Working_set_limit = (*limit*) *queuename*
SHOW *option*
SHOW All
SHOW LImits_supported
SHOW LONG Queue [*queuename [username]*]
SHOW Managers
SHOW Parameters
SHOW Queue [*queuename [username]*]
SHUtdown [*seconds*]
STArt CXbatch
STArt Queue *queuename*

STOp Queue *queuename*

SUspend Request *request-list*

qmapmgr

Add Mid *mid principal-name*

Add Name *name principal-mid*

CHange Name *mid principal-name*

CReate

Delete Mid *mid*

Delete Name *alias*

Exit

Get Mid *principal-name*

Get Name *mid*

Help

Quit

Show

